



Fusion 3C

Cena brutto	23 711,94 zł
Cena netto	19 278,00 zł
Dostępność	Dostępny
Czas wysyłki	24 godziny
Numer katalogowy	123.866
Producent	Leister

Opis produktu

Dzięki krótkiej, zwartej konstrukcji zagwarantowana jest łatwa obsługa. Wszechstronne zastosowanie dzięki obrotowemu butowi spawalniczemu (360°), przede wszystkim w budownictwie ziemnym. Podgrzewanie masy tworzywa następuje przy użyciu powietrza, którego temperatura regulowana jest za pomocą potencjometru.

Dane techniczne:

Napięcie: 230V
Moc: 2800W
Częstotliwość: 50 HZ
Przepływ powietrza (20 s. C) ok. 350 l/m
Wydajność zgrzewania (HDPE) 1,6 - 3,5 kg/h
Domieszka zgrzewająca: PE, PP
Grubość ścianki: 8 - 25 mm
Folie: >1 mm
Spoiwo: Ø 3 i 4 mm

Waga: 6,9 kg
Długość: 588 mm

LEISTER

The suitable welding shoe for every application

FUSION 2/3/3C/WELDPLAST S2



Seam geometries



Fillet weld seam



V-seam / X-seam



Overlap seam



Corner outside seam



Corner seam



Leister Integrated Air System (IA): The air guidance is integrated into the welding shoe. This enables the turning of the shoe 360° into every desired welding and seam position.


 K-5/6 IA Fillet weld, 5/6 mm Article No.: 145.943	 K-8/10 IA Fillet weld, 8/10 mm Article No.: 145.944	 K-15 IA Fillet weld, 15 mm Article No.: 145.812	 K-20 IA Fillet weld, 20 mm Article No.: 145.940	 K-25 IA Fillet weld, 25 mm Article No.: 145.816
 K-30 IA Fillet weld, 30 mm Article No.: 145.817	 V-5/6 IA V-seam, 5/6 mm Article No.: 145.912	 V-8/10 IA V-seam, 8/10 mm Article No.: 145.915	 V-12 IA V-seam, 12 mm Article No.: 145.907	 V-15 IA V-seam, 15 mm Article No.: 145.903
 UBL-25 IA Overlap seam, 25 mm Article No.: 145.896	 UBL-30 IA Overlap seam, 30 mm Article No.: 145.947	 UBL-35 IA Overlap seam, 35 mm Article No.: 145.897	 V-20 IA V-seam, 20 mm Article No.: 145.909	 V-25 IA V-seam, 25 mm Article No.: 145.916
 V-30 IA V-seam, 30 mm Article No.: 145.905	 CO-8 IA Corner outside, 8 mm Article No.: 146.643	 CO-10 IA Corner outside, 10 mm Article No.: 146.645	 CO-12 IA Corner outside, 12 mm Article No.: 146.649	 CO-15 IA Corner outside, 15 mm Article No.: 146.651
 CL-14 IA Corner seam, 14 mm Article No.: 145.811	 CS-20 IA Corner seam, 20 mm Article No.: 145.488	 45° Angled adapter WP S2 Article No.: 139.460	 90° Angled adapter WP S2 Article No.: 139.461	 Welding rod de-roller for 1 roll Article No.: 144.095
 Pre-heat reflector Article No.: 136.231				

Leister Technologies AG

Switzerland / www.leister.com

Wydajność Extruderów LEISTER

kg/h



Wydajność zależy od zastosowanego tworzywa!