

LEISTER

PLASTIC WELDING

Hot-Air Hand Tools

2019/2020



General accessories



www.leister.com/accessories

Product overview

Hot-air hand tools

									
Type	TRIAC ST	TRIAC AT	ELECTRON ST	HOT JET S	SOLANO AT	GHIBLI AW	GHIBLI	HOTWIND	FORTE S3
Voltage V~	230 / 120	230 / 120	230 / 120	230 / 120	230	120/230	120/230	230	3 × 230 / 3 × 400
Max. power W	1600	1600	2400 / 3400	460	2300	1800 / 2300	1500 / 2000	3700	10 000
Temperature °C	40 – 700	40 – 620	40 – 650	40 – 600	50 - 650	65 – 620	40 – 600	20 – 650	20 – 650
Size mm (L × W × H) Handle (Ø)	338 × 90 56	338 × 90 56	338 × 90 56	235 × 70 40	270 × 75 × 240 45	280 × 90 × 220 45	195 × 85 × 160 57	332 × 106 × 179	390 × 132 85
Weight kg (without cord)~	1.0	1.0	1.1	0.4	0.75	1.1	0.9	2.2	4.4
Integrated blower	✓	✓	✓	✓	✓	✓	✓	✓	✓
Digital display		✓			✓	✓		✓ (SYSTEM)	
Conformity mark	CE	CE	CE	CE	CE	CE	CE		CE
Approval mark	§ K	§ K	§ K	§ K	K	§		K	§
Protection class	□	□	□	□	□	□	□	□	□
Applications									
Outdoor use	✓	✓	✓	✓		✓			✓
Roofing 	✓	✓	✓	✓					
Billboards / Tarpaulins 	✓	✓		✓	✓				
Civil engineering / Tunneling / Landfills 	✓	✓	✓						
Plastic fabrication 	✓	✓		✓					
Flooring / Interior design 	✓	✓	✓	✓					
Shrinking 	✓	✓	✓	✓	✓	✓	✓	✓	✓
Special applications 					✓	✓	✓	✓	✓



Hot-air hand tools and Blower


						
Type	AIRSTREAM ST	ROBUST	WELDING PEN R / S	DIODE PID / S	MINOR	LABOR S
Voltage V~	230	3 × 230 / 3 × 400	230	230	230	230
Max. power W	215	250	1000	1600 / 2000	100	800 / 900
Temperature °C			20 – 600	20 – 600		20 – 600
Size mm (L × W × H) Handle (Ø)	600 × 250 × 362	255 × 221	270 × 43 32	265 × 57 40	250 × 95 64	180 × 54 32
Weight kg (without cord)~	24	8.0	1.0	1.15	1.15	0.15
Integrated blower	✓	✓			✓	
Digital display			✓ (R)	✓ (PID)		
Conformity Mark	CE		CE	CE	CE	CE
Approval mark						
Protection Class	⊕	⊕	⊞	⊞	⊞	⊞
Applications						
Indoor use	✓	✓	✓	✓	✓	✓
Roofing 						
Billboards / Tarpaulins 						
Civil engineering / Tunneling / Landfills 						
Plastic fabrication 	✓	✓	✓	✓	✓	✓
Flooring / Interior design 						
Shrinking 	✓			✓		✓



Accessories Hot-Air Hand Tools

Wide slot nozzles

Wide slot nozzle: a x b mm, e° angled, f° bent



Wide slot nozzle Ø21.3 mm

	TRIAC ST / AT	ELECTRON ST	HOT JET S	GHIBLI / GHIBLI AW	SOLANO AT	WELDING PEN R / S	DIODE PID / S	LABOR S
 105.549 10 x 2 mm, 15° angled, 30° bent			•					•
 107.141 15 x 2 mm, 15° angled, 30° bent			•					•
 105.559 20 x 2 mm, straight			•					•
 107.142 ¹⁾ 20 x 2 mm, 30° angled			•					•
 105.556 20 x 2 mm, 75° angled			•					•
 105.070 25 x 1 mm, straight			•					•
 105.066 30 x 1 mm, straight			•					•
 105.548 40 x 5 mm, straight			•					•
 105.547 50 x 8 mm, straight			•					•
 105.039 80 x 1 mm, straight			•					•
 105.036 100 x 1 mm, straight			•					•

Wide slot nozzle Ø31.5 mm

	TRIAC ST / AT	ELECTRON ST	HOT JET S	GHIBLI / GHIBLI AW	SOLANO AT	WELDING PEN R / S	DIODE PID / S	LABOR S
 105.475 20 x 2 mm, straight	•							•
 NEW 105.477 20 x 2 mm, straight, 150 mm length	•							•
 107.123 ¹⁾ 20 x 2 mm, 15° angled	•							•
 107.125 ¹⁾ 20 x 2 mm, 60° angled, foil left	•							•
 105.503 ¹⁾ 20 x 2 mm, 60° angled, foil right	•							•
 107.124 ¹⁾ 20 x 2 mm, 75° angled	•							•
 124.999 20 x 3 mm, 15° angled, 120° bent, foil left	•							•
 105.500 20 x 3 mm, 15° angled, -120° bent, foil right	•							•
 105.492 20 x 2 mm, 15° angled, 120° bent	•							•
 105.487 ¹⁾ 20 x 2 mm, -15° angled, 30° bent	•							•
 160.858 20 x 9 mm, straight	•							•
 105.485 25 x 2 mm, straight	•							•
 105.494 30 x 2 mm, 15° angled	•							•
 128.535 30 x 2 mm, 45° angled	•							•
 105.526 40 x 2 mm, straight	•							•

Wide slot nozzle Ø31.5 mm

		TRIAC ST / AT	ELECTRON ST	HOT JET S	GIBLI / GIBLI AW	SOLANO AT	WELDING PEN R / S	DIODE PID / S	LABOR S
	107.132 ¹⁾ 40 x 2 mm, 15° angled	•						•	
	107.133 40 x 2 mm, 15° angled, perforated	•						•	
	107.143 40 x 2 mm, 15° angled, with stop plate	•						•	
	107.135 40 x 2 mm, 15° angled, PTFE-coated	•						•	
	107.130 40 x 2 mm, 60° angled	•						•	
	105.531 40 x 2 mm, 90° angled,	•						•	
	105.527 40 x 8 mm, 30° bent	•						•	
	107.129 ¹⁾ 60 x 2 mm, 15° angled, for Bitumen	•						•	
	107.131 ¹⁾ 80 x 2 mm, 15° angled, for Bitumen	•						•	

Wide slot nozzle Ø36.5 mm

	105.435 20 x 2 mm, straight, without clamps				•	•			
	106.998 ¹⁾ 20 x 2 mm, 15° angled				•	•			
	106.999 ¹⁾ 40 x 2 mm, -15° angled				•	•			
	108.086 40 x 2 mm, straight, without clamps				•	•			
	107.261 70 x 4 mm, straight, without clamps				•	•			

Wide slot nozzle Ø36.5 mm

	108.078 100 x 4 mm, straight				•	•			
	105.982 150 x 4 mm, straight				•	•			

Wide slot nozzle Ø50.0 mm


	107.134 40 x 2 mm, straight, for tape welding		•						
	105.961 42 x 11 mm, length 300 mm		•						
	107.258 ¹⁾ 70 x 10 mm, straight, for Bitumen, without clamps		•						
	142.281 ²⁾ 74 x 3 mm, with scraper		•						
	107.653 ²⁾ 75 x 2 mm, 20° angled, for Bitumen		•						
	106.057 100 x 4 mm, straight, without clamps		•						
	106.060 150 x 6 mm, straight, without clamps		•						
	107.270 150 x 12 mm, straight, without clamps		•						
	106.061 300 x 6 mm, straight		•						

¹⁾ POS cardboard box available (please refer to p. 18 / 19)

²⁾ Tool stand 151.068 recommended (please refer to p. 14)

Tubular nozzles

Tubular nozzle: $\varnothing a$ mm, c mm, e° angled




Tubular nozzle $\varnothing 21.3$ mm

	TRIAC ST / AT	ELECTRON ST	HOT JET S	GHIBLI / GHIBLI AW	SOLANO AT	WELDING PEN R / S	DIODE PID / S	LABOR S
 105.624 $\varnothing 4$ mm, 45 mm, straight			•					•
 107.144 ¹⁾ $\varnothing 5$ mm, 41 mm, 15° angled, suitable for speed welding nozzle			•					•
 105.566 $\varnothing 5$ mm, 45 mm, straight, suitable for speed welding nozzle			•					•
 105.567 $\varnothing 5$ mm, 150 mm, straight, suitable for speed welding nozzle			•					•
 131.867 $\varnothing 5$ mm, 30 x 60 mm, 90° bent, suitable for speed welding nozzle			•					•
 105.618 $\varnothing 7$ mm, 30 mm, straight			•					•
 107.145 $\varnothing 10$ mm, 45 mm, straight			•					•
 107.152 $\varnothing 12$ mm, 25 x 50 mm, 90° angled			•					•
 105.641 $\varnothing 21.3$ mm, 33 x 45 mm, 90° angled			•					•

Soldering nozzle $\varnothing 21.3$ mm

 105.614 3 x 1.5 mm, 30 mm, straight			•					•
 107.148 3 x 1.5 mm, 40 mm, 45° angled			•					•

Tubular nozzle: $\varnothing a$ mm, c x d mm, e° angled



Soldering nozzle $\varnothing 21.3$ mm

	TRIAC ST / AT	ELECTRON ST	HOT JET S	GHIBLI / GHIBLI AW	SOLANO AT	WELDING PEN R / S	DIODE PID / S	LABOR S
 107.147 $\varnothing 1.5$ mm, 30 mm, 45° angled			•					•
 107.146 $\varnothing 2$ mm, 40 mm, 45° angled			•					•
 107.150 $\varnothing 2.5$ mm, 45 mm, 45° angled			•					•
 107.151 $\varnothing 4$ mm, 45 mm, 45° angled			•					•
 107.149 $\varnothing 7$ mm, 40 mm, 20° angled			•					•

Tubular nozzle $\varnothing 31.5$ mm

 107.000 $\varnothing 5$ mm, 27 - 39 mm, straight (triplicate)	•							•
 100.303 ¹⁾ $\varnothing 5$ mm, 37 mm, 15° angled, suitable for speed welding nozzle	•							•
 105.576 $\varnothing 5$ mm, 30 x 60 mm, 90° bent, suitable for speed welding nozzle	•							•
 105.575 $\varnothing 5$ mm, 100 mm, straight, suitable for speed welding nozzle	•							•
 106.982 $\varnothing 5$ mm, 150 mm, -15° angled , suitable for speed welding nozzle	•							•
 105.429 $\varnothing 5$ mm, 200 mm, straight, suitable for speed welding nozzle	•							•

Tubular nozzle Ø31.5 mm

		TRIAC ST / AT	ELECTRON ST	HOT JET S	GHIBLI / GHIBLI AW	SOLANO AT	WELDING PEN R / S	DIODE PID / S	LABOR S
	107.128 Ø10 mm, 44 mm, straight	•						•	
	105.514 Ø14 mm, 25 x 50 mm, 90° angled	•						•	
	111.711 Ø18 mm, 70 mm, straight	•						•	

Tubular nozzle Ø36.5 mm

	107.154 ¹⁾ Ø5 mm, 41 mm, straight, suitable for speed welding nozzle				•	•			
	107.006 Ø5 mm, 130 mm, straight				•	•			
	105.818 Ø5 mm, 150 mm, straight, suitable for speed welding nozzle				•	•			
	105.454 Ø9 mm, 50 mm, straight, without clamps				•	•			
	105.455 Ø9 mm, 102 mm, straight, without clamps				•	•			
	107.002 Ø12 mm, 25 x 50 mm, 90° angled				•	•			
	107.003 Ø12 mm, 25 x 50 mm, 90° angled, without clamps				•	•			
	105.462 Ø21.3 mm, 58 mm, straight, without clamps				•	•			
	105.446 Ø25 mm, 25 x 95 mm, 90° angled				•	•			

Tubular nozzle Ø50.0 mm

		TRIAC ST / AT	ELECTRON ST	HOT JET S	GHIBLI / GHIBLI AW	SOLANO AT	WELDING PEN R / S	DIODE PID / S	LABOR S
	107.229 Ø20 mm, without clamps	•							
	107.256 Ø48 mm, 85 x 165 mm, 90° angled	•							


Tubular nozzle M14

	116.519 Ø5 mm, 43 mm, straight, suitable for speed welding nozzle						•		
	105.622 Ø5 mm, 43 mm, 15° angled, suitable for speed welding nozzle						•		

¹⁾ POS cardboard box available (please refer to p. 18 / 19)

Speed welding nozzles

Speed welding nozzle: a mm



Speed welding nozzle Ø8.0 mm

		TRIAC ST / AT	ELECTRON ST	HOT JET S	GHIBLI / GHIBLI AW	SOLANO AT	WELDING PEN R / S	DIODE PID / S	LABOR S
	106.989 ³⁾ Round Ø3 mm Profile D 	•	•	•	•	•	•	•	•
	105.431 ¹⁾³⁾ Round Ø3 mm, with narrow air slit Profile D 	•	•	•	•	•	•	•	•
	160.550 ¹⁾³⁾ Round Ø3 mm, with narrow air slit, tip bent Profile D 	•	•	•	•	•	•	•	•
	106.990 ³⁾ Round Ø4 mm Profile D 	•	•	•	•	•	•	•	•
	105.432 ¹⁾³⁾ Round Ø4 mm, with narrow air slit Profile D 	•	•	•	•	•	•	•	•
	106.991 ¹⁾³⁾ Round Ø5 mm Profile D 	•	•	•	•	•	•	•	•
	105.433 ¹⁾³⁾ Round Ø5 mm, with narrow air slit Profile D 	•	•	•	•	•	•	•	•
	159.848 ¹⁾³⁾ Round Ø5 mm, with narrow air slit, tip bent Profile D 	•	•	•	•	•	•	•	•
	156.470 ³⁾ Round Ø5 mm, tip bent Profile D 	•	•	•	•	•	•	•	•
	107.137 ³⁾ Tape 8 x 2 mm Profile C 	•	•	•	•	•	•	•	•
	107.139 ³⁾ Tape 12 x 4.5 mm 	•	•	•	•	•	•	•	•
	106.992 ³⁾ Triangle 5.7 x 3.7 mm Profile A 	•	•	•	•	•	•	•	•

Speed welding nozzle Ø8.0 mm

	106.993 ³⁾ Triangle 7 x 5 mm Profile B 	•	•	•	•	•	•	•	•
---	--	---	---	---	---	---	---	---	---

Smoothing nozzle Ø8.0 mm

	165.937 ³⁾ for welded seams in corners and curves	•	•	•	•	•	•	•	•
---	--	---	---	---	---	---	---	---	---

Tacking nozzle Ø8.0 mm

	106.996 ³⁾ Ø8 mm	•	•	•	•	•	•	•	•
---	---------------------------------------	---	---	---	---	---	---	---	---

Tacking nozzle M14

	106.988 M14						•		
---	-----------------------	--	--	--	--	--	---	--	--

Drawing nozzle (M14)

	113.876 Round Ø3 mm, without tacking tip Profile D 						•		
	113.666 Round Ø3 mm, with tacking tip Profile D 						•		
	113.874 Round Ø4 mm, without tacking tip Profile D 						•		
	113.399 Round Ø4 mm, with tacking tip Profile D 						•		
	126.552 Round Ø4 mm, for Fluoroplastics Profile D 						•		
	113.877 Triangle, 5.7 x 3.7 mm, without tacking tip Profile A 						•		

¹⁾ POS cardboard box available (please refer to p. 18 / 19)

³⁾ suitable tubular nozzle required



Drawing nozzle (M14)

		TRIAC ST / AT	ELECTRON ST	HOT JET S	GHIBLI / GHIBLI AW	SOLANO AT	WELDING PEN R / S	DIODE PID / S	LABOR S
	113.670 Triangle, 5.7 x 3.7 mm, with tacking tip Profile A 						•		
	106.986 Triangle, 7 x 5 mm, without tacking tip Profile B 						•		
	106.987 Triangle, 7 x 5.5 mm, without tacking tip 						•		

Speed welding nozzle Ø31.5 mm

		TRIAC ST / AT	ELECTRON ST	HOT JET S	GHIBLI / GHIBLI AW	SOLANO AT	WELDING PEN R / S	DIODE PID / S	LABOR S
	113.183 Tape 21 x 4 mm 	•						•	
	107.136 Tape 25 x 4 mm 	•						•	



Profile size in mm

Profile A	Profile B	Profile C	Profile D
			

Welding rods please refer to p. 16




Sieve reflector: a x b mm, e° angled




—	TRIAC ST / AT
—	ELECTRON ST
•	HOT JET S
—	GHIBLI / GHIBLI AW
—	SOLANO AT
—	WELDING PEN R / S
—	DIODE PID / S
•	LABOR S

107.339
17 x 34 mm, 90° angled




107.314
33 x 27 mm, 90° angled,
without clamps



106.128
13 x 5 x 10 mm,
without clamps


107.326
150 x 26 x 44 mm,
without clamps

Shell reflector $\varnothing 36.5$ mm




107.340
250 x 46 x 62 mm,
without clamps

107.331
Ø72 x 70 mm



107.324 ³⁾
13 x 10 mm, 90° angled, suitable
tubular nozzle required



www.leister.com

Sieve reflector Ø21.3 mm

		TRIAC ST / AT	ELECTRON ST	HOT JET S	GHIBLI / GHIBLI AW	SOLANO AT	WELDING PEN R / S	DIODE PID / S	LABOR S
	107.310 35 x 20 mm, 75° angled			•					•
	107.311 50 x 34 mm, 75° angled			•					•

Sieve reflector Ø31.5 mm

	107.338 35 x 20 mm, 90° angled, without clamps	•							•
	107.337 50 x 34 mm, 75° angled, without clamps	•							•
	106.161 50 x 34 mm, straight	•							•
	118.845 60 x 57 x 45 mm, straight, without clamps	•							•

Sieve reflector Ø36.5 mm

	107.309 35 x 20 mm, 75° angled, without clamps				•	•			
	107.308 50 x 34 mm, 75° angled, without clamps				•	•			
	112.068 50 x 34 mm, straight, without clamps				•	•			
	127.137 60 x 57 x 45 mm, straight, without clamps				•	•			
	107.318 Ø65 mm, straight				•	•			
	107.319 Ø65 mm, straight, without clamps				•	•			

Sieve reflector Ø50.0 mm

	107.327 75 x 70 x 90 mm, straight, without clamps		•						
	107.333 150 x 110 x 137 mm, straight, without clamps		•						
	106.127 Ø65 mm, straight, without clamps		•						



Special nozzles

Ironig nozzle Ø21.3 mm

		TRIAC ST / AT	ELECTRON ST	HOT JET S	GHIBLI / GHIBLI AW	SOLANO AT	WELDING PEN R / S	DIODE PID / S	LABOR S
	107.305 15 x 25 mm Profile dimension			•					•
	114.734 40 x 20 mm Profile dimension for ski repairs			•					•

De-horning nozzle Ø36.5 mm

		TRIAC ST / AT	ELECTRON ST	HOT JET S	GHIBLI / GHIBLI AW	SOLANO AT	WELDING PEN R / S	DIODE PID / S	LABOR S
	107.007 Ø20 mm, 58 mm, straight				•	•			

Protection nozzle Ø31.5 mm

		TRIAC ST / AT	ELECTRON ST	HOT JET S	GHIBLI / GHIBLI AW	SOLANO AT	WELDING PEN R / S	DIODE PID / S	LABOR S
	157.717 Ø23 mm, protection ring Ø80 mm	•							•

Protection nozzle Ø36.5 mm

		TRIAC ST / AT	ELECTRON ST	HOT JET S	GHIBLI / GHIBLI AW	SOLANO AT	WELDING PEN R / S	DIODE PID / S	LABOR S
	158.474 Ø23 mm, protection ring Ø80 mm				•	•			

Protection nozzle Ø50.0 mm

		TRIAC ST / AT	ELECTRON ST	HOT JET S	GHIBLI / GHIBLI AW	SOLANO AT	WELDING PEN R / S	DIODE PID / S	LABOR S
	160.842 Ø44 mm, Protection ring Ø100 mm	•							

Adapter Ø21.3 mm

		TRIAC ST / AT	ELECTRON ST	HOT JET S	GHIBLI / GHIBLI AW	SOLANO AT	WELDING PEN R / S	DIODE PID / S	LABOR S
	143.831 to M14			•					•

Adapter Ø31.5 mm

		TRIAC ST / AT	ELECTRON ST	HOT JET S	GHIBLI / GHIBLI AW	SOLANO AT	WELDING PEN R / S	DIODE PID / S	LABOR S
	143.833 to M14	•							•

Adapter Ø50.0 mm

		TRIAC ST / AT	ELECTRON ST	HOT JET S	GHIBLI / GHIBLI AW	SOLANO AT	WELDING PEN R / S	DIODE PID / S	LABOR S
	122.924 to Ø36.5 mm	•							

Adapter (M14)

		TRIAC ST / AT	ELECTRON ST	HOT JET S	GHIBLI / GHIBLI AW	SOLANO AT	WELDING PEN R / S	DIODE PID / S	LABOR S
	141.375 to Ø21.3 mm						•		
	127.726 to M14, 30° angled						•		
	127.727 to M14, 45° angled						•		

Welding mirror Ø31.5 mm

		TRIAC ST / AT	ELECTRON ST	HOT JET S	GHIBLI / GHIBLI AW	SOLANO AT	WELDING PEN R / S	DIODE PID / S	LABOR S
	107.344 Ø135 mm	•						•	

Welding mirror Ø36.5 mm


		TRIAC ST / AT	ELECTRON ST	HOT JET S	GHIBLI / GHIBLI AW	SOLANO AT	WELDING PEN R / S	DIODE PID / S	LABOR S
	107.345 Ø135 mm				•	•			

Welding mirror Ø50.0 mm

		TRIAC ST / AT	ELECTRON ST	HOT JET S	GHIBLI / GHIBLI AW	SOLANO AT	WELDING PEN R / S	DIODE PID / S	LABOR S
	107.346 Ø270 mm	•							
	107.347 74 x 12 x 520 mm, edges rounded, PTFE-coated	•							

Pressure roller

a mm (material of the roller)



	106.976 ¹⁾ 28 mm (PTFE), with ball bearing	•	•	•	•	•	•	•	•	•
	140.161 ¹⁾ 28 mm (silicone), with ball bearing	•	•	•	•	•	•	•	•	•
	140.598 Spare roll for 140.161	•	•	•	•	•	•	•	•	•
	140.160 ¹⁾ 40 mm (silicone), with ball bearing	•	•	•	•	•	•	•	•	•
	140.599 Spare roll for 140.160	•	•	•	•	•	•	•	•	•
	106.974 80 mm (silicone)	•	•	•	•	•	•	•	•	•
	106.972 ¹⁾ 6 mm (brass), with ball bearing	•	•	•	•	•	•	•	•	•
	106.971 7 mm (brass), for welding rod Ø2 - 4 mm	•	•	•	•	•	•	•	•	•
	106.970 ¹⁾ 7 mm (brass), for welding rod Ø4 - 5 mm	•	•	•	•	•	•	•	•	•
	106.981 16 mm (steel & silicone)	•	•	•	•	•	•	•	•	•
	108.190 16 mm (silicone)	•	•	•	•	•	•	•	•	•

Roll

	111.788 Spare roll for 108.190 and 106.981	•	•	•	•	•	•	•	•	•
--	---	---	---	---	---	---	---	---	---	---

Planer and spare blades

	111.346 Chamfer planer for Z spare blades for sealing sheets	•	•	•	•	•	•	•	•	•
	111.188 Spare blade for 111.346	•	•	•	•	•	•	•	•	•
	106.966 Hand grooving tool	•	•	•	•	•	•	•	•	•
	106.968 Spare blade for 106.966	•	•	•	•	•	•	•	•	•
	151.188 ¹⁾ Chamfer planer for T-joints for sealing sheets	•	•	•	•	•	•	•	•	•
	150.809 Hand grooving tool «GROOVY», 3.5 mm for weldable floor coverings	•	•	•	•	•	•	•	•	•

Various accessories

	138.314 ¹⁾ Seam probe tester for overlap seams	•	•	•	•	•	•	•	•	•
	154.026 Scraper blade	•	•	•	•	•	•	•	•	•
	165.734 3 spare blades for 154.026	•	•	•	•	•	•	•	•	•
	154.259 Contour scraper	•	•	•	•	•	•	•	•	•

¹⁾ POS cardboard box available (please refer to p. 18 / 19)

Various accessories

		TRIAC ST / AT	ELECTRON ST	HOT JET S	GHIBLI / GHIBLI AW	SOLANO AT	WELDING PEN R / S	DIODE PID / S	LABOR S
	137.855 ¹⁾ Leister cutter with holster and 4 spare blades	•	•	•	•	•	•	•	•
	138.902 Hooked blades for 137.855 (10 dispenser with 10 pcs = 100 pcs)	•	•	•	•	•	•	•	•
	138.539 Straight-edge blades for 137.855 (10 dispenser with 10 pcs = 100 pcs)	•	•	•	•	•	•	•	•
	151.382 ¹⁾ Inside corner tool	•	•	•	•	•	•	•	•
	153.009 Plastfix	•	•	•	•	•	•	•	•
	152.676 Leister weld seam template	•	•	•	•	•	•	•	•
	159.514 Seam inspection template	•	•	•	•	•	•	•	•
	157.544 Leister Universal scissors 260 mm with special shaft grinding	•	•	•	•	•	•	•	•
	116.798 ¹⁾ Brass brush	•	•	•	•	•	•	•	•
	142.647 Brass brush Ø3 mm	•	•	•	•	•	•	•	•
	106.997 Ø6 mm rotary burr for drilling machine, for car repairs	•	•	•	•	•	•	•	•

Cutting tools

	106.969 ¹⁾ Quarter Moon Knife including leather case, 100 mm stainless steel blade	•	•	•	•	•	•	•	•
	122.541 ¹⁾ Trimming guide to use with 106.969	•	•	•	•	•	•	•	•
	117.000 Trimming knife with 0.6 mm spacer for vinyl and linoleum with 5 spare blades included	•	•	•	•	•	•	•	•

Cutting tools

	117.005 5 spare blades for 117.000	•	•	•	•	•	•	•	•
	117.007 1 universal spacer 0.6 mm for 117.000	•	•	•	•	•	•	•	•

Cable extension

	160.353 Cable cord roller 25 m, 1 x CEE 400 V, 2 x 230 V EU-plug, 5 x 2.5 mm²	•	•	•	•	•	•	•	•
	161.152 Cable cord roller 25 m, 1 x CEE 400 V, 2 x 230 V CH-plug, 5 x 2.5 mm²	•	•	•	•	•	•	•	•
	161.207 Cable cord roller 25 m, 1 x CEE 400 V, 2 x 230 V FR, BE, CZ, PL-plug, 5 x 2.5 mm²	•	•	•	•	•	•	•	•
	164.048 Cable cord roller 45 m, 4 x 230 V EU-plug, 3 x 2.5 mm²	•	•	•	•	•	•	•	•
	160.015 Cable extension cord 15 m, 5 x 2.5 mm² CEE 400 V	•	•	•	•	•	•	•	•
	159.239 Cable extension cord 15 m, 3 x 2.5 mm² with 230 V EU-plug	•	•	•	•	•	•	•	•

Tool rest

	151.068 Tool stand	•							
	107.348 Tool rest	•	•	•					•
	103.401 Tool rest replaced by 107.348		•						•

¹⁾ POS cardboard box available (please refer to p. 18 / 19)

Heater tube protection


		TRIAC ST / AT	ELECTRON ST	HOT JET S	GHIBLI / GHIBLI AW	SOLANO AT	WELDING PEN R / S	DIODE PID / S	LABOR S
	148.933 Heater tube protection (only for ELECTRON ST)		•						

Heater tube (M14)

	143.332 Heater tube (M14) for screw-on nozzles (only for TRIAC ST till April 2017)	•							
	156.092 Heater tube (M14) for screw-on nozzles (only for TRIAC ST after May 2017)	•							
	144.134 Heater tube (M14) for screw-on nozzles (only for TRIAC AT)	•							

Plastic case

	116.586 Plastic case for TRIAC ST/AT and ELECTRON ST	•	•						
	151.167 Plastic case for SOLANO AT and GHIBLI AW				•	•			



Welding rods



Welding accessories PE

	Profile	Farbe	kg
104.283 Welding rod HDPE	A	■	3
104.294 Welding rod HDPE	A	□	3
104.284 Welding rod HDPE	B	■	5
104.299 Welding rod HDPE	B	□	5
106.650 Welding rod HDPE	C	□	1
104.300 Welding rod LDPE	A	■	3
161.612 Welding rod HDPE	D	■	2
116.918 Welding rod HDPE	D	■	2

Welding accessories PP

104.287 Welding rod PP	A	■	3
104.301 Welding rod PP	A	■	3
106.642 Welding rod PPs, flame resistant	A	■	3
104.288 Welding rod PP	B	■	5
126.356 Welding rod PP	C	□	2
161.611 Welding rod PP	D	■	2

Welding accessories PVC

104.296 Welding rod PVC-U	A	□	3
104.278 Welding rod PVC-U	A	■	3
106.641 Welding rod PVC-U	A	■	3
104.280 Welding rod PVC-U	B	■	5
104.279 Welding rod PVC-U	B	■	5
109.925 Welding rod PVC-U	D	■	4
104.302 Welding rod PVC-P (soft)	A	□	3

Welding accessories ABS

104.295 Welding rod ABS	A	□	3
113.587 Welding rod ABS	A	■	3
107.027 Welding band ABS	C	□	1

Welding accessories div.

104.297 Welding rod PA	A	■	3
104.298 Welding rod PC	A	□	3
104.313 Welding rod PC / ABS / ALPHA (Honda)	A	■	3
104.308 Welding rod PUR	A	■	3
106.654 Welding band Xenoy	C	■	2
104.304 Welding rod PVDF	A	□	3
104.303 Welding rod POM	A	□	3
112.185 PC/PBTX Xenoy welding rod	A	□	3

Welding accessories

107.036 Test bundle bodywork welding rods, each consisting of profile A pieces of 37 cm single marked 6x HDPE, 6x PP, 6x PA, 6x PC, 6x ABS, 6x PCABS / ALPHA Honda, 6x PC / PBTP / Xenoy	
107.037 Test bundles standard each consisting pieces of 37 cm single marked 5x PVC-U, 5x PVC-P, 5x PP, 5x ABS, 5x HDPE, 3x PC, 3x PA, 3x POM, 3x LDPE, 3x PC / ABS / ALPHA Honda, 3x PC / PBTP / Xenoy	
107.040 Test bundle welding band each consisting of profile C pieces of 37 cm single marked 9x HDPE 8x 2 mm white, 9x PP, 8x 2 mm natural, 9x ABS, 8x 2 mm white, 9x PC / PBTP / Xenoy grey	
144.095 Welding rod dispenser	

Profile size in mm

Profile A 	Profile B 	Profile C 	Profile D
----------------------	----------------------	----------------------	----------------------

POS Rack



For ordering POS rack,
please contact salesupport@leister.com

POS Sales items

Wide slot nozzle Ø21.3 mm

		TRIAC ST / AT	ELECTRON ST	HOT JET S	GHIBLI / GHIBLI AW	SOLANO AT	WELDING PEN R / S	DIODE PID / S	LABOR S
	146.721 20 x 2 mm, 30° angled			•					•

Wide slot nozzle Ø31.5 mm

	122.836 20 x 2 mm, 15° angled	•							•
	150.126 20 x 2 mm, 60° angled, foil left	•							•
	146.892 20 x 2 mm, 60° angled, foil right	•							•
	150.130 20 x 2 mm, 75° angled	•							•
	137.825 20 x 2 mm, -15° angled, 30° bent	•							•
	121.129 40 x 2 mm, 15° angled	•							•
	150.004 60 x 2 mm, 15° angled, for Bitumen	•							•
	156.207 80 x 2 mm, 15° angled, for Bitumen	•							•

Wide slot nozzle Ø36.5 mm

	121.857 20 x 2 mm, 15° angled			•	•				
	109.743 40 x 2 mm, -15° angled			•	•				

Wide slot nozzle Ø50.0 mm

		TRIAC ST / AT	ELECTRON ST	HOT JET S	GHIBLI / GHIBLI AW	SOLANO AT	WELDING PEN R / S	DIODE PID / S	LABOR S
	157.727 70 x 10 mm, straight, for Bitumen, without clamps	•							

Tubular nozzle Ø21.3 mm

	153.790 Ø5 mm, 41 mm, 15° angled, suitable for speed welding nozzle		•						•
---	---	--	---	--	--	--	--	--	---

Tubular nozzle Ø31.5 mm

	152.966 Ø5 mm, 37 mm, 15° angled, suitable for speed welding nozzle	•							•
---	---	---	--	--	--	--	--	--	---

Tubular nozzle Ø36.5 mm

	152.195 Ø5 mm, 41 mm, straight, suitable for speed welding nozzle			•	•				
---	---	--	--	---	---	--	--	--	--

Speed welding nozzle Ø8.0 mm

	155.370 Round Ø3 mm, with narrow air slit Profile D ●	•	•	•	•	•	•	•	•
	160.550 Round Ø3 mm, with narrow air slit, tip bent Profile D ●	•	•	•	•	•	•	•	•
	155.371 Round Ø4 mm, with narrow air slit Profile D ●	•	•	•	•	•	•	•	•
	154.402 Round Ø5 mm Profile D ●	•	•	•	•	•	•	•	•
	155.367 Round Ø5 mm, with narrow air slit Profile D ●	•	•	•	•	•	•	•	•
	159.848 Round Ø5 mm, with narrow air slit, tip bent Profile D ●	•	•	•	•	•	•	•	•

Pressure roller

		TRIAC ST / AT	ELECTRON ST	HOT JET S	GHIBLI / GHIBLI AW	SOLANO AT	WELDING PENR / S	DIODE PID / S	LABOR S
	155.455 28 mm (PTFE), with ball bearing	•	•	•	•	•	•	•	•
	155.372 28 mm (silicone), with ball bearing	•	•	•	•	•	•	•	•
	156.441 40 mm (silicone), with ball bearing	•	•	•	•	•	•	•	•
	155.456 6 mm (brass), with ball bearing	•	•	•	•	•	•	•	•
	155.457 7 mm (brass), for welding rods Ø4 - 5 mm	•	•	•	•	•	•	•	•

Planer


	156.203 Chamfer planer for T-joints for sealing sheets	•	•	•	•	•	•	•	•
---	---	---	---	---	---	---	---	---	---


Various accessories

	155.461 Seam probe tester for overlap seams	•	•	•	•	•	•	•	•
	137.855 Leister cutter with holster and 4 spare blades	•	•	•	•	•	•	•	•
	155.460 Inside corner tool	•	•	•	•	•	•	•	•
	155.459 Brass brush	•	•	•	•	•	•	•	•

Cutting tools

	106.969 Quarter Moon Knife including leather case, 100 mm stainless steel blade	•	•	•	•	•	•	•	•
	109.742 Trimming guide to use with 106.969	•	•	•	•	•	•	•	•





Leister Technologies AG
 Galileo-Strasse 10
 CH-6056 Kaegiswil / Switzerland
 phone: +41 41 662 74 74
 fax: +41 41 662 74 16
 leister@leister.com

Leister Technologies LLC
 Itasca, IL 60143 / USA
 phone: +1 855 534 7837
 info.usa@leister.com

Leister Technologies Ltd.
 Shanghai 201 109 / PRC
 phone: +86 21 6442 2398
 leister@leister.cn

Leister Technologies KK
 Osaka 564-0051 / Japan
 phone: +81 6 6310 62 00
 sales-japan@leister.com

Leister Technologies Benelux BV
 3991 CE Houten / Nederland
 phone: +31 (0)30 2199888
 info@leister.nl

Leister Technologies Italia s.r.l.
 20090 Segrate / Italia
 phone: +39 02 2137647
 sales@leister.it

Leister Technologies India Pvt
 600 041 Chennai / India
 phone: +91 44 2454 3436
 info@leister.in

Leister Technologies
 Deutschland GmbH
 D-58093 Hagen / Germany
 phone: +49-(0)2331-95940
 info.de@leister.com

Our close worldwide network of more than 130 Sales and Service Centres in more than 100 countries.

Europe:

Andorra
 Austria
 Belgium
 Cyprus
 Denmark
 Finland
 France
 Germany
 Greece
 Iceland
 Ireland
 Italy
 Luxembourg
 Malta
 Monaco
 Netherlands
 Norway
 Portugal
 Liechtenstein
 San Marino
 Spain

Sweden
 Switzerland
 Turkey
 United Kingdom
 Vatican
 Albania
 Armenia
 Azerbaijan
 Belarus
 Bosnia-Herzegovina
 Bulgaria
 Croatia
 Czech Republic
 Estonia
 Georgia
 Hungary
 Kosovo
 Latvia
 Lithuania
 Macedonia
 Moldova
 Montenegro

Poland
 Romania
 Russia
 Serbia
 Slovakia
 Slovenia
 Ukraine

Americas:

Canada
 Mexico
 USA
 Belize
 Costa Rica
 El Salvador
 Guatemala
 Honduras
 Nicaragua
 Panama
 Argentina
 Bolivia
 Brazil

Chile
 Colombia
 Ecuador
 Peru
 Venezuela

Central Asia:

Kazachstan
 Kyrgyzstan
 Tajikistan
 Turkmenistan
 Uzbekistan

Middle East:

Bahrain
 Iraq
 Israel
 Jordan
 Qatar
 Saudi Arabia
 U.A.E

Africa:

Algeria
 Botswana
 Egypt
 Ivory Coast
 Kenya
 Lesotho
 Libya
 Malawi
 Morocco
 Mozambique
 Namibia
 North Sudan
 South Africa
 Swaziland
 Tunisia
 Zambia
 Zimbabwe

Asia Pacific:

Bangladesh
 China
 Hong Kong
 India
 Indonesia
 Japan
 Korea
 Macao
 Malaysia
 Mongolia
 Philippines
 Singapore
 Sri Lanka
 Taiwan
 Thailand
 Vietnam

Oceania:

Australia
 New Zealand

© Copyright by Leister, Switzerland

Your Leister Sales and Service Center: